

Model 1207F Accelerometer




- MEMS DC Response
- Durable Cable
- Low Cost
- Reliable Performance



The **Model 1207F** accelerometer is a small, compact uniaxial device designed for vehicle impact and road testing. Its mechanical overload stops provide high shock protection in rugged applications. Featuring ranges from 50g to 1000g and frequency response to 3000 Hz, this sensor is easily mounted in hard to get places on vehicles under test.

dimensions




FEATURES

- MEMS Sensing Element
- $\pm 50g$ to $\pm 1000g$ Dynamic Range
- 2-10 VDC Excitation
- 0 to 50°C Temperature Compensation
- ± 40 mV Zero Acceleration Output
- Rugged Strain Relief
- Mechanical Overload Stops

APPLICATIONS

- Crash Testing
- Impact testing
- Off-Road Testing
- Road Testing



Model 1207F Accelerometer

performance specifications

All values are typical at +24°C, 100Hz and 10Vdc excitation unless otherwise stated. Measurement Specialties reserves the right to update and change these specifications without notice. Standard product parameters are described in PSC-1004 for Plug & Play DC Accelerometers.

Parameters

DYNAMIC

	±50	±100	±200	±500	±1000	Notes
Range (g)	±50	±100	±200	±500	±1000	
Sensitivity (mV/g) ¹	2	0.9	0.7	0.4	0.15	@10Vdc Excitation
Frequency Response (Hz)	0-800	0-1500	0-1800	0-2700	0-4000	±1dB
Phase Response	0-300	0-500	0-500	0-1000	0-2000	<±5°
Natural Frequency (Hz)	2000	3000	4000	6000	7000	
Non-Linearity (%FSO)	±1	±1	±1	±1	±1	
Transverse Sensitivity (%)	<3	<3	<3	<3	<3	
Damping Ratio	0.6	0.6	0.6	0.3	0.1	
Shock Limit (g)	5000	5000	5000	5000	5000	

ELECTRICAL

Zero Acceleration Output (mV)	±40					Differential
Excitation Voltage (Vdc)	2 to 10					
Input Resistance (Ω)	2400-5000					
Output Resistance (Ω)	2400-5000					
Insulation Resistance (MΩ)	>100					@50Vdc
Residual Noise (μV RMS)	10					Maximum
Ground Isolation	Isolated from Mounting Surface					

ENVIRONMENTAL

Thermal Zero Shift (%FSO/°C)	±0.05
Thermal Sensitivity Shift (%/°C)	-0.20 ±0.05
Operating Temperature (°C)	-40 to +100
Compensated Temperature (°C)	-20 to +85
Storage Temperature (°C)	-40 to +100
Humidity	Epoxy Sealed

PHYSICAL

Case Material	Anodized Aluminum
Cable	PFA Insulated Leads, Braided Shield, Polyurethane Jacket
Weight (grams)	3.0
Mounting	2x #4 or M3 Screws
Mounting Torque	4.0 lb-in (0.5 N-m)
AWG	#28

¹ Output is ratiometric to excitation voltage

Wiring color code: +Excitation = Red; -Excitation = Black; +Output = Green; -Output = White;

Calibration supplied: CS-FREQ-0100 NIST Traceable Amplitude Calibration from 20Hz to ±1dB Frequency Response Limit

Supplied accessories: 2x #4-40 (1/4" length) Socket Head Cap Screw and Washer

Optional accessories: 101 Three Channel DC Signal Conditioner Amplifier
140 Auto-zero Inline Amplifier

ordering info

PART NUMBERING Model Number+Range+Cable Length

1207F-XXXX-ZZZ

| | Cable (360 is 360 inches)
| Range (0050 is 50g)

Example: 1207F-0050-360

Model 1207F, 50g, 360" (30ft) Cable

联系方式



深圳市亿为测控电子有限公司
Shenzhen Bill-Well Measurement & Control Electronics Co., Ltd.

广东省深圳市南山区创业路怡海广场东座2407 邮编: 518000

电话: +86 755 2641 9890 传真: +86 755 2641 9680

电子邮箱: sales@bill-well.com

www.bill-well.com

深圳市亿为测控电子有限公司