

### 316L SS Pressure Sensor Small Profile 0 – 100mV Output Gage, Absolute

#### 86 Series

The 86 series is a small profile, media compatible, piezoresistive silicon pressure sensor packaged in a 316L stainless steel housing. The 86 is designed for o-ring mounting and OEM applications where compatibility with corrosive media is required.

The sensing package utilizes silicone oil to transfer pressure from the 316L stainless steel diaphragm to the sensing element.



#### FEATURES

- O-Ring Mount
- -40°C to +125°C Operating Temperature Range
- Up to  $\pm 0.1\%$  Pressure Non Linearity
- 1.0% Interchangeable Span (provided by gain set resistor)
- Solid State Reliability

#### APPLICATIONS

- Medical Instruments
- Process Control
- Fresh & Waste Water Measurements
- Partial Vacuum Gas Measurement
- Pressure Transmitters
- Tank Level Systems (RV & Industrial)

# 86 Series

## Product Definition

| Model                | Pressure Ranges                        | Type (G = Gage<br>A = Absolute<br>D = Differential,<br>V = Vacuum<br>Gage) | Span (typ)         | Supply  |         | Operating<br>Temperature | Unique Feature                   |
|----------------------|--|--|--------------------|---------|---------|--------------------------|----------------------------------|
|                      |  |  |                    | Voltage | Current |                          |                                  |
| <a href="#">86U</a>  | 0 – 5, 15, 30, 50,<br>100, 300, 500psi | A, G   | See<br>Sensitivity |         | 1.5mA   | -40°C to +125°C          | Small profile<br>No substrate    |
| <a href="#">86C</a>  | 0 – 5, 15, 30, 50,<br>100, 300, 500psi | A, G   | 100mV              |         | 1.5mA   | -40°C to +125°C          | Small profile<br>6-Pad substrate |
| <a href="#">86CV</a> | 0 – 5, 15, 30, 50,<br>100, 300, 500psi | A, G   | 100mV              | 10Vdc   |         | -40°C to +125°C          | Small profile<br>4-Pad substrate |
| <a href="#">86VC</a> | 0 – 15, 30, 50, 100,<br>300, 500psi    | V  | 100mV              |         | 1.5mA   | -40°C to +125°C          | Small profile<br>6-Pad substrate |

## 联系方式



深圳市亿为测控电子有限公司  
Shenzhen Bill-Well Measurement & Control Electronics Co., Ltd.

广东省深圳市南山区创业路怡海广场东座2407 邮编：518000

电话：+86 755 2641 9890 传真：+86 755 2641 9680

电子邮箱：sales@bill-well.com