



- Multi-components, 3 channels Force sensor
- Ranges 50 to 500 N (10 to 100 lbf)
- Aluminum body
- High adaptability to rod
- Optional built-in amplifier version

DESCRIPTION

The FN7080 is installed in place of the original gear knob on the gear stick of a vehicle and will measure the force required to change gear. Force is measured either in two or three directions. An adapter coupled with an interface collar allows a simple and rapid fitting of the FN7080 to the majority of vehicles.

The sensor's geometry and size mean that it is as ergonomic as the original gear knob. The ease of mounting enables the FN7080 to be used on a vehicle or on a test bench. An optional version provides direct high level output and makes the FN7080 a favorite among European car builders.

Measurement Specialties, Inc. have many years of experience as a designer and manufacturer of sensing solutions to the automotive industry and can supply standard or custom sensors for specific uses and testing environments.

Consult Measurement Specialties, Inc. Engineering Department for a custom solution to your application.

FEATURES

- 2 and 3 axes measurements
- Fits most gear sticks
- Compact and ergonomic design
- Optional high level output
- Exists in many optional designs

APPLICATIONS

- On-board vehicle equipment
- Test bench equipment
- Robotics and effectors
- Laboratory and Research

STANDARD RANGES

Ranges in N	50	100	200	300	500
Ranges in lbf	10	20	40	60	100

FN7080 Gear Stick Load Cell

PERFORMANCE SPECIFICATIONS

All values are typical at temperature 20±1° C

Parameters	
Operating Temperature Range (OTR)	-20 to 80° C [-4 to 176° F]
Compensated Temperature Range (CTR)	0 to 60° C [32 to 140° F]
Zero Shift in CTR	<0.5% F.S. / 50° C [100° F]
Sensitivity Shift in CTR	<1% of reading / 50° C [100° F]
Ranges (F.S.)	50 to 500 N [10 to 100 lbf]
Over-Range	
Without Damage	1.5 x F.S.
Without Destruction	3 x F.S.
Accuracy	
Combined non-linearity & hysteresis	≤±3% F.S.
Cross effect	≤3% F.S.

Electrical Characteristics


Model	FN7080	FN7080-A1	FN7080-A2
Supply Outage	5Vdc	10 to 30Vdc	±15Vdc (±12 to ±18Vdc)
F.S. Output	±2mV/V	±2V ±5% F.S.	±5V ±5% F.S.
Zero Offset	±5% F.S.	2.5V ±5% F.S.	0V ±5% F.S.
Input Impedance/Consumption	350 to 700Ω	<50mA	50mA
Output Impedance	350 to 700Ω	<10Ω	<10Ω
Insulation under 50Vdc	≥100MΩ	≥100MΩ	≥100MΩ

Notes

1. Electrical Termination: three Shielded Cable length 2m
2. Materials body in aluminium, casing in anodized aluminum
3. Protection Index: IP50


FN7080 Gear Stick Load Cell

DIMENSIONS & WIRING SCHEMATIC (IN METRIC)




Wiring Schematic (each cable)


FN7080



FN7080-A1



FN7080-A2



FN7080 Gear Stick Load Cell

OPTIONS

A1 : Amplified Tension output with unipolar power supply
A2 : Amplified Tension output with bipolar power supply
ET1 : CTR -20 to 100° C OTR = CTR
ET2 : CTR -40 to 120° C OTR = CTR
L00M : special cable length, replace "00" with total length in meters

ORDERING INFO

FN7080
└───
└─── Model

联系方式



深圳市亿为测控电子有限公司
Shenzhen Bill-Well Measurement & Control Electronics Co., Ltd.

广东省深圳市南山区创业路怡海广场东座2407 邮编：518000
电话：+86 755 2641 9890 传真：+86 755 2641 9680
电子邮箱：sales@bill-well.com