

# Point Sensing RTD Probe

- Variety of Configurations
- Tip Sensitive
- Quick Time Response
- Single Element
- Cable or Leadwire Options



The **Point Sensing RTD Probe** is constructed with a rigid stainless steel sheath with an element embedded into an aluminum tip. The aluminum tip provides faster time response. These sensors are typically designed for use in plenums and ducts within HVAC systems. They can also be utilized whenever a quick time response in a non-corrosive low pressured environment is needed.


## FEATURES

- Sheath Styles:
  - » Rigid Stainless Steel
- Elements, Single:
  - » Platinum
- Sheath Diameter:
  - » Stem: .250"
  - » Tip: .188"
- Leadwire/Cable Options

## APPLICATIONS

- HVAC

## dimensions



# Point Sensing RTD Probe

## performance specifications

### Insulation Resistance:

Single Element:  
1,000 megohms @ 500 VDC, leads to case

### Time Constant (typical in 3 ft/sec moving water):

Single Element: 2.0 seconds

### Repeatability:

Less than  $\pm .06\%$  change in ice point resistance after  
10 consecutive cycles between ice point and 250°C

### Long Term Stability:

Less than  $\pm .2\%$  ice point resistance shift  
after 1,000 hours at 250°C

### Self Heating:

10 mW/C in water moving 3 feet/sec

### Vibration:

Withstands 5 to 500 Hz at 3 g-level peak for  
3 hours. Per ASTM E 644, Sec. 10.

### Shock:

Withstands 50 g-level peak sine wave shock of  
11 milliseconds duration. Per ASTM E 644, Sec. 11

## ordering info

### Point Sensing RTD Probe

Model	Sheath Style	Temperature Range	
500M	Standard Stainless Steel with Aluminum Tip	-50 to 250°C (-58 to 482°F)	
Model	Element	Accuracy	Temperature Coefficient
P2A	Platinum	100 Ohm $\pm .06\%$ at 0°C	.00385
P2B	Platinum	100 Ohm $\pm .12\%$ at 0°C	.00385
P2C	Platinum	100 Ohm $\pm .5\%$ at 0°C	.00385
Model	Leadwires, Element Configuration	Typical Color Code	
2S	Two Wire, Single	Red/White	
3S	Three Wire, Single	Red/Red/White	
4S	Four Wire, Single	Red/Red/White/White	
Model	'L' Sheath Length		
---	Define 'L' Length in Inches (12 = 12.0")		
Model	'Y' Leadwire/Cable Options		
N	No Options, Stranded TFE Leadwires (36.0" Standard)		
W	Leadwire Options		

## 联系方式



深圳市亿为测控电子有限公司  
Shenzhen Bill-Well Measurement & Control Electronics Co., Ltd.

广东省深圳市南山区创业路怡海广场东座2407 邮编：518000

电话：+86 755 2641 9890 传真：+86 755 2641 9680

电子邮箱：sales@bill-well.com