

SR Series



CABLE-ACTUATED POSITION SENSORS



- User Adjustable Stroke Range to 175 inches
- Rugged Polycarbonate Enclosure
- 0-10 VDC, 4-20mA, Voltage Divider, Encoder
- **In Stock for Fast Delivery!**

The SR1 series are rugged, low-cost, high performance string pots built for wet environments and outdoor applications. Designed for the rigors of outdoor construction equipment or the demands of a factory floor, this series is the perfect low-cost solution for OEM and stocking distributors.

Internal programmable circuitry of the SR1M (4-20mA) and SR1V (0-10V) gives the customer a one-size-fits-all approach for many applications. Both models ship factory calibrated to the full stroke range but the output signal can be easily re-scaled to match any stroke down to 1 inch (25 mm).

Connect To Product Datasheets Below

SR1A

 Voltage Divider



10K ohm • IP67

SR1E


Incremental Encoder



IP67 Protection

SR1M

4..20mA



Adj. Stroke Range

SR1V

0..10Vdc
0..5Vdc



Adj. Stroke Range

联系方式



深圳市亿为测控电子有限公司
Shenzhen Bill-Well Measurement & Control Electronics Co., Ltd.

广东省深圳市南山区创业路怡海广场东座2407 邮编：518000

电话：+86 755 2641 9890 传真：+86 755 2641 9680

电子邮箱：sales@bill-well.com

www.bill-well.com

深圳市亿为测控电子有限公司