

# PT5 Series



CABLE-ACTUATED POSITION SENSORS



250 (0.15m) Linear Measurement Range


- Industrial Grade
- Hard-Anodized Aluminum Enclosure
- IP67/NEMA 6 Protection

The PT5 Series is an excellent solution for high acceleration and high-cycle applications such as die-casting, injection molding or crash testing. Thousands of configurations are available to exactly meet application requirements and lead times are frequently 1-2 weeks.

Cable-Actuated Sensors are easy and quick to install as critical alignment is not required. They retract to a height a fraction of the measurement range and provide a highly repeatable, high-resolution output.

## Connect To Product Datasheets Below

### Analog Output



PT5A	PT5AV	PT5MA	PT5DC
Voltage Divider	Position & Velocity	4..20mA 0..20mA	0..5 Vdc 0..10Vdc
500, 1K, 5K, 10K ohm & bridge circuit	voltage divider position & DC velocity signals	4..20mA (2-wire) & 0..20mA (3-wire)	0..5, 0..10, -5..+5 & -10..+10 Vdc
<a href="#">click ► here</a>	<a href="#">click ► here</a>	<a href="#">click ► here</a>	<a href="#">click ► here</a>

### Digital Output



PT5E	PT5232	PT5CN	PT5DN
Incremental Encoder	RS232	CANbus J1939	DeviceNET®
10-250 ppi	16-bit absolute position	16-bit absolute position	16-bit absolute position
<a href="#">click ► here</a>	<a href="#">click ► here</a>	<a href="#">click ► here</a>	<a href="#">click ► here</a>

### 联系方式



深圳市亿为测控电子有限公司  
Shenzhen Bill-Well Measurement & Control Electronics Co., Ltd.

广东省深圳市南山区创业路怡海广场东座2407 邮编：518000

电话：+86 755 2641 9890 传真：+86 755 2641 9680

电子邮箱：sales@bill-well.com